

according to Regulation (EC) No 1907/2006

ParaBond Adhesive B

Revision date: 20.04.2015 Print date: 22.02.2018 Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ParaBond Adhesive B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

for dental use only

1.3. Details of the supplier of the safety data sheet

Company name: COLTENE/Whaledent AG Street: Feldwiesenstrasse 20 Place: CH-9450 Altstätten +41 (71) 75 75 300 Telephone: Telefax: +41 (71) 75 75 301 e-mail: info.ch@coltene.com Internet: www.coltene.com Responsible Department: Regulatory Affairs

msds@coltene.com

1.4. Emergency telephone +41 (0) 44 251 51 51 - Tox Info Suisse (24 h)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Hazard Statements:

Highly flammable liquid and vapour.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.

Precautionary statements

Keep container tightly closed.

Additional advice on labelling

Medical devices as defined in Directive 93/42/EEC and which are invasive or used in direct physical contact with the human body, are exempted from the provisions of Regulation (EC) No 1272/2008 (CLP/GHS) usually if they are in the finished state and intended for the final user.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Revision No. 2 GB - FN



according to Regulation (EC) No 1907/2006

ParaBond Adhesive B

Revision date: 20.04.2015 Print date: 22.02.2018 Page 2 of 6

Hazardous components

| CAS No | Chemical name | | | | |
|---------|---|--------------|--|--|--|
| | EC No Index No REACH No | | | | |
| | Classification according to Regulation (EC) No. 1272/2008 [CLP] | | | | |
| 64-17-5 | ethanol, ethyl alcohol | | | | |
| | 200-578-6 | 603-002-00-5 | | | |
| | Flam. Liq. 2; H225 | | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After inaestion

Seek medical advice.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray. Foam. Extinguishing powder. Carbon dioxide (CO2). Sand.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Wipe up with absorbent material (eg. cloth, fleece). Clear contaminated areas thoroughly.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes.

for professional use only Keep out of the reach of children.

Observe instructions for use.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Further information on handling

After use replace the closing cap immediately.

7.2. Conditions for safe storage, including any incompatibilities



according to Regulation (EC) No 1907/2006

ParaBond Adhesive B

Revision date: 20.04.2015 Print date: 22.02.2018 Page 3 of 6

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Further information on storage conditions

Recommended storage temperature: 4 - 8 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|---------|-----------|------|-------|-----------|---------------|--------|
| 64-17-5 | Ethanol | 1000 | 1920 | | TWA (8 h) | WEL |
| | | - | - | ĺ | STEL (15 min) | WEL |

8.2. Exposure controls

Protective and hygiene measures

When using do not eat, drink or smoke.

Eye/face protection

Framed glasses.

Hand protection

Single-use gloves.

Skin protection

Lab apron.

Respiratory protection

Provide adequate ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Test method

Changes in the physical state

Initial boiling point and boiling range: 78 - 80 °C
Flash point: 15 °C
Lower explosion limits: 3.5 vol. %
Upper explosion limits: 19 vol. %
Density: 0.84 g/cm³
Water solubility: easily soluble.

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

heat.

10.5. Incompatible materials

Oxidizing agents.

SECTION 11: Toxicological information



according to Regulation (EC) No 1907/2006

ParaBond Adhesive B

Revision date: 20.04.2015 Print date: 22.02.2018 Page 4 of 6

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | | | |
|---------|-------------------------|---------------|-----------|---------|--------|--------|--|
| | Exposure route | Dose | | Species | Source | Method | |
| 64-17-5 | ethanol, ethyl alcohol | | | | | | |
| | oral | LD50 mg/kg | 6200 | Rat | IUCLID | | |
| | inhalative (4 h) vapour | LC50 | 95,6 mg/l | Rat | RTECS | | |

Irritation and corrosivity

Hazards identification: Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

| CAS No | Chemical name | | | | | | | |
|---------|--------------------------|---------------------------|-----------|---------------|--------|--------|--|--|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method | | |
| 64-17-5 | ethanol, ethyl alcohol | | | | | | | |
| | Acute crustacea toxicity | EC50 9268 - 14221 mg/l | 48 h | Daphnia magna | IUCLID | | | |

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|---------|------------------------|---------|
| 64-17-5 | ethanol, ethyl alcohol | -0,31 |

Further information

According to the criteria of the EC-classification and labelling "dangerous for the environment" (93/21/EEC) the material/product is not to be classified as dangerous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Limited quantity:LQ4



according to Regulation (EC) No 1907/2006

ParaBond Adhesive B

Revision date: 20.04.2015 Print date: 22.02.2018 Page 5 of 6

Hazard No: 33

Other applicable information (land transport)

Special provisions: 274

E3 : 1 D/E

Special provisions: 274 601 640C

E2 : 2

Special provisions: 640C Special provisions: 144 601

Marine transport (IMDG)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Limited quantity:3 LEmS:F-E, S-D

Other applicable information (marine transport)

Special provisions: 274, 330, 944 Special provisions: 944 Special provisions: 144, 330

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Limited quantity Passenger:1 L

IATA-packing instructions - Passenger: 305
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 307
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2 : Y305 60 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Additional information

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.



according to Regulation (EC) No 1907/2006

ParaBond Adhesive B

Revision date: 20.04.2015 Print date: 22.02.2018 Page 6 of 6

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)